



Square Type □



Circular Type ○

## Main Features:

- Philips SMD LED chips, MeanWell/Inventronics driver
- Die casting aluminum housing with reliable powder coating for harsh outdoor environments
- External air-flow fins for maximum heat dissipation
- UV-stabilized PC lens designed to last
- Easy installation for retrofits and new construction, with options of surface mounted and pendant mounted
- Suitable for Wet locations
- Motion Sensor (Optional)

Model No.	Size	Power	Voltage	Luminous Flux	CCT Optional	CRI	Beam Angle
EFS-CPC50WS □	L225xW225xH100mm L8.86"xW8.86"xH3.94"	50W	AC100-277V	5500lm	3000K/5000K	≥70	140 Degree
EFS-CPC50WC ○	φ290xH115mm φ11.42"xH4.53"						
EFS-CPC75WS □	L225xW225xH100mm L8.86"xW8.86"xH3.94"	75W	AC100-277V	8250lm	3000K/5000K	≥70	140 Degree
EFS-CPC75WC ○	φ290xH115mm φ11.42"xH4.53"						
EFS-CPC100WS □	L305xW305xH100mm L12"xW12"xH3.94"	100W	AC100-277V	11000lm	3000K/5000K	≥70	140 Degree
EFS-CPCI00WC ○	φ385xH100mm φ15.16"xH3.94"						
EFS-CPCI20WS □	L305xW305xH100mm L12"xW12"xH3.94"	120W	AC100-277V	13200lm	3000K/5000K	≥70	140 Degree
EFS-CPCI20WC ○	φ385xH100mm φ15.16"xH3.94"						

## Applications:

- Parking garages
- Petroleum stations
- Security areas
- Corridors
- Walkways

